


FHC Series

CHARACTERISTICS

- Low R_{dc} with flat wire design
- Low copper losses at high frequency
- Magnetic shielded structure
- Quantity: 400pcs

APPLICATION

- High current DC/DC converter
- LC filter



Inductance	Tolerance	Temperature Rise Current	Current	DC Resistance Typ.	DC Resistance Max.
	±20%	32.0	65.0	0.35	0.40
	±20%	30.0	50.0	0.67	0.85
	±20%	27.0	35.0	0.90	1.10
	±20%	25.0	25.0	1.80	2.00
	±20%	23.0	22.0	2.60	2.90
	±20%	20.0	17.5	3.30	3.60
	±20%	17.0	16.0	4.90	5.40
	±20%	13.0	15.0	7.00	7.70
	±20%	12.0	14.0	8.40	9.20
	±20%	13.0	12.0	5.90	6.50
	±20%	12.0	10.5	7.80	8.60
	±20%	11.0	9.50	9.10	10.0
	±20%	10.0	9.00	11.2	12.3

Part No	Inductance	Tolerance	Temperature Rise Current	Current	DC Resistance Typ.	DC Resistance Max.
FHC1365-150M	15.0	±20%	9.00	8.00	14.8	16.3
FHC1365-180M	18.0	±20%	7.50	7.50	22.0	24.2
FHC1365-220M	22.0	±20%	6.00	6.50	24.7	27.2
FHC1365-330M	33.0	±20%	5.50	5.50	30.5	33.6

Test Frequency : Inductance : 100KHz /0.1V.

Operating Temperature : -40 °C to +125 °C

Temperature Rise Current: the actual value of DC current when the temperature rise is $\Delta T 50^{\circ}\text{C}$

Saturation Current that will cause initial inductance to drop approximately 30%

